


NK-6120

3.5 inch Bay Trail J1900 Single Board

01 Feature

- Intel® Celeron® J1900 processor, Quad-core, base frequency 2.0GHz, up to 2.42GHz, TDP 10W
- Support 1x DDR3L-1333MHz SO-DIMM slot, up to 8GB
- Support VGA, HDMI, LVDS/eDP Dual-display
- 2 x Giga-bit Ethernet
- 1 x USB3.0 port, 5 x USB2.0 ports
- 1 x RS232/485, 1 x RS232, 4 x TTL
- 1 x M.2-2242, 1 x Mini-PCle slot with nano-SIM card socket
- 12~24V power input, lockable DC-IN phoenix terminal block


02 I/O Layout



03 Specification


Project		Content
Processor System	CPU	Intel® Celeron® J1900 processor, Quad-core, base frequency 2.0GHz, up to 2.42GHz, TDP 10W
	Chipset	Intel® SoC integrated
	BIOS	AMI 64Mb UEFI BIOS
Memory	Technology	Single Channel(Non-ECC) DDR3L 1333MHz, up to 8GB
	Slot	1 x DDR3L SO-DIMM slot
Storage	SATA	1 x SATA2.0 port
	M.2	1 x M.2-2242 M Key SSD slot(SATA2.0 Signal)
Graphic	Controller	Intel HD graphics integrated
Audio	Codec	Realtek ALC897codec
Rear I/O	Display	1 x VGA, resolution up to 2560x1600@60Hz
		1 x HDMI, resolution to 1920x1080@60Hz
	Ethernet	2 x GbE(RJ45), Realtek 8111H controller
	USB	1 x USB3.0(5Gbps), 1 x USB2.0(480Mbps)
	Button	1 x Power Button(White for power on,Blink for sleep mode,Off for power off)
	Indicators	1 x SATA LED(Red), 1 x Power LED(Green)
Internal I/O	Display	1 x LVDS, dual channel 18/24bit, resolution up to 1920x1200@60Hz
		1 x eDP1.3, max resolution up to 3840x2160@60Hz(share connector with LVDS)
	Audio	1 x Audio wafer(Mic-in/Line-out, 2*5pin)
	USB	2 x USB2.0 wafer(1*4pin), 2 x USB2.0 wafer(1 x 2*5pin)
	Serial Port	1 x RS232/485 wafer(2*5pin), 1 x RS232 wafer(2*5pin),4 x TTL wafer(2*8pin)
	Fan	1 x Smart Fan wafer(1*4pin)
	SMbus	1 x SMbus wafer(1*4pin)
	LPC	1 x LPC header for debug
	GPIO	1 x 8bit GPIO(2*5pin)
	Others	1 x Front panel wafer(2*5pin)(Power LED, HDD LED, Power button, Reset button)
Expansion Slots	Mini-PCIe slot	1 x Mini-PCIe slot with Nano-SIM socket (PCIe/USB2.0)
Watchdog Timer	Output&Interval	System reset, programmable from 1~255 seconds
Power	Type	12~24V DC input, +/-10% tolerance
	Interface	1 x 2-pin phoenix terminal block
	Power Consumption	16.3W (Idle mode), 17.5W(Typical mode)
O.S Support	MS Windows	Windows7/10
	Linux	Linux
Mechanism	尺寸 Dimensions	(L)146mm x (W)102mm
	Gross Weight	0.14kg
Environment	Temperature	Operating: -10°C ~60°C with SSD,Storage: -40°C ~85°C
	Humidity	5~95% (Non-condensing)
	Vibration	5~500Hz, 3Grms operating

04 Block Diagram



05 Mechanical Drawing

Unit: mm



06 Order Information

Part No.	Model	Description
F32.612003.10.NEK	NK-6120	3.5", Baytrial, J1900, DDR3L SO-DIMM, M.2-2242(SATA2.0), Standard, compose, 2*COM Cable, 1*SATA Cable

07 Packing List

Part No.	Qty	Description
KF0.001140.00.L54	2	COM Cable,2*5pin wafer to DB9 cable, length=250mm
KF0.001049.00.L54	1	SATA Cable,signal and power cable, length=150mm
JF7.000041.00.D03	1	2-pin termianl block,pitch 5.08mm

08 Optional Accessories

Part No.	Description
C2Z.612001.0A.NDJ	Heatsink for NK-6120
C3Z.NKEB01.10.NDJ	AEB-4COM00, 2 x RS485/422/232(DB9) ,2 x RS232 wafer I/O expansion kit
C3Z.000001.00.NDJ	CM-060W-CWT0, 12V/60W adapter, 180cm power cord
C3Z.000002.00.NDJ	CM-090W-HKA, 12V/84W adapter, 180cm power cord
KF0.001140.00.L54	COM Cable,2*5pin wafer to DB9 cable, length=250mm
KF0.001047.00.L54	USB cable, 1*4pin wafer to USB2.0 type-A cable, length=150mm
KF0.001048.00.L54	USB cable, 2 x USB2.0 type-A Y cable with bracket, length=150mm
KF0.000949.00.Y09	Audio Cable, 2*5pin wafer to Mic-in/Line-out cable, length=300mm